

CLAIM LISTING

This listing of claims will replace all prior versions, and listings of claims in the application:

IN THE CLAIMS

1. (Previously Presented) A conductive lid adapted to function as a heat sink for an integrated circuit, said conductive lid comprising:
  - a recessed portion adapted to receive a die of said integrated circuit;
  - a foot portion extending from the top of said conductive lid to a surface adapted to be coupled to a substrate of said integrated circuit; and
  - a through-hole located in said foot portion, said through-hole being tapered and adapted to receive an adhesive to secure said conductive lid to said substrate of said integrated circuit;wherein said adhesive secures said conductive lid to said substrate of said integrated circuit by applying a force along a wall of said tapered through-hole, said wall extending substantially vertically from said substrate.
2. – 3. (Canceled)
4. (Previously Presented) The conductive lid of claim 1 wherein said through-hole comprises a multi-diameter through-hole.
5. (Canceled)
6. (Original) The conductive lid of claim 1 wherein said through-hole is formed by injection molding.
7. (Original) The conductive lid of claim 1 wherein said through-hole is formed by drilling.

8. (Original) The conductive lid of claim 1 wherein said foot portion extends around said recessed portion.

9. (Original) The conductive lid of claim 8 further comprising a plurality of through-holes positioned in said foot portion.

10. (Original) The conductive lid of claim 9 wherein said plurality of holes are symmetrically spaced around said foot portion.

11. (Previously Presented) An integrated circuit having a heat sink, said integrated circuit comprising:

- a substrate;

- a die positioned on said substrate;

- a conductive lid positioned over said die and coupled to said substrate, said conductive lid having a foot portion extending from a top of said conductive lid to said substrate and comprising at least one multi-diameter through-hole,

- wherein said through-hole comprises a frustum-shaped through-hole; and

- an adhesive extending from said substrate into said through-hole;

- wherein said adhesive secures said conductive lid to said substrate by applying a force along a surface of said through-hole extending substantially vertically from said substrate.

12. – 13. (Canceled)

14. (Original) The integrated circuit of claim 11 wherein said through-hole comprises a conical through-hole.

15. – 16. (Canceled)

17. (Previously Presented) The integrated circuit of claim 11 wherein said adhesive material comprises a thermally conductive epoxy.

18. (Canceled)

19. (Original) The integrated circuit of claim 11 further comprising a thermal grease positioned between said die and said conductive lid.

20. (Original) The integrated circuit of claim 11 further comprising underfill positioned between said substrate and said conductive lid.

21-37. (Canceled)